

**Name** Nimbus Pendant (with single ES lampholder & IP44 Rated Enclosure)

**Materials** Metal Wire, Spun Metal, Acrylic, Plastic, Steel, Paint

**Suspension** Single ES E27 Lampholder, 120mm Dia. Decorative Low Profile Canopy and Three Core Electrical Flex

**Dimensions** 475 Ø x 320 H (mm)

**Lamp Type** 240Volt: Single ES E27 Lamp  
(See table at bottom of page for lamp options and maximum wattages.)

Check lamp type for suitability with dimming. Please ensure lamps are purchased from quality lamp manufacturers such as Philips or Osram. Low quality lamps may not perform as well. Lamps not included. Frosted, warm colour temperature, decorative lamps recommended. To change lamps, ALWAYS switch off power to light fitting, then unscrew lamp from lampholder and replace with same type. Make sure lamp is secured into lampholder prior to light operation.

**Warning** This pendant is rated to IP44 ONLY, designed for use under awnings or verandas.

#### Installation

1 Be extremely careful when handling the pendant shade as painted surfaces are delicate and can scuff easily. Please leave protective plastic cover on shade while preparing for installation.

**WARNING: DO NOT terminate three core flex into low profile ceiling plate, as this is NOT IP44 rated under any circumstances. Flex MUST be terminated into an appropriately IP rated enclosure remotely. (Not supplied with this fitting.)**



2 Slide low profile canopy cover plate down flex. With two people, (*one to hold the pendant in position,*) Terminate flex into appropriate IP rated enclosure. (*See warning above.*) Once three core flex is wired, secure ceiling plate to ceiling with appropriate screws, using the various fixing holes available to suit site specific needs. Slide canopy cover plate back up flex and secure to back plate using earth magnets supplied. Ensure the cord grip has been re-tightened after making adjustment.

3 Do not apply force to shades or fixture and remember to remove protective plastic cover prior to turning on.

**PLEASE READ THIS DATA SHEET CAREFULLY PRIOR TO COMMENCING ANY INSTALLATION OF LIGHT FITTINGS. PLEASE CONTACT SATELIGHT IF YOU HAVE ANY QUESTIONS.**



## nimbus pendant (240 volt) IP44



Check lamp type for suitability with dimming.  
All dimensions are in millimetres.

#### Important Safety Instructions

- Please ensure all installation steps are conducted by certified electrical contractors.
- Lit lamp is extremely hot! Only use switch or plug when turning on or off.
- **Always TURN OFF fitting and allow lamp to cool down before replacing lamp. Only switch on fitting once lamp has been correctly secured into lampholder.**
- Keep fixture away from flammable objects or materials that may burn.
- Remove dust and insects from lamp and surfaces regularly.

#### Cleaning

Do not use abrasive cleaning materials on fixture. Do not wipe suspension set with wet cloth. Dust only. Please be aware that the finishes are delicate and can scuff easily.