

**Name** Nord XL  
**Materials** Spun Metal, Plastic, Steel, Paint  
**Suspension** Electronic Driver, Lamp, Low profile ceiling canopy and Electrical Flex  
**Dimensions** 530 Ø x 275 H (mm)  
**Lamp Type** 24 Volt Replaceable lamp

Check lamp type for suitability with your dimming system.


#### Installation

- 1 Be extremely careful when handling the pendant shade as materials are delicate and can scuff easily. Please leave protective plastic cover on shade while preparing for installation.
- 2 Using a qualified electrical contractor, connect electronic driver or transformer to mains power, connect electrical cable from fixture to driver using the terminal block connected to the ceiling canopy and heat shrink. Install ceiling canopy back bracket to ceiling with appropriate screws. Trim suspension cable to approximate length, allowing additional length for final adjustment. Slide suspension cable through cable adjuster, located on ceiling canopy cover.
- 3 Slide front plate of canopy up the flex to meet the back plate and fix with magnetic connectors. Once attached, tighten off-centre cord grip on the ceiling canopy cover securely.
- 4 Once suspension and shade is secured, undo skirt on lampholder and feed through central hole of the shade. Once in place, screw lampholder skirt back on. Do not over-tighten as this may strip the thread on the lampholder.
- 5 If you need to lower or raise the pendant, unscrew top thread two to three turns on the cable adjuster, push in adjuster barrel on cable adjuster to allow cable to slide through. The suspension cable needs to be under tension and remove weight from the electrical flex, which must be slack. Please make sure adjuster cap is tightened after adjustment and trim off excess suspension cable once adjusted.
- 6 Do not apply force to shades or fixture and remember to remove protective plastic cover prior to turning on.

PLEASE READ THIS DATA SHEET CAREFULLY PRIOR TO COMMENCING ANY INSTALLATION OF LIGHT FITTINGS. PLEASE CONTACT SATELIGHT IF YOU HAVE ANY QUESTIONS.



### nord XL pendant (24 Volt)



Check lamp type for suitability with dimming.  
 All dimensions are in millimetres.

#### Important Safety Instructions

- Please ensure all installation steps are conducted by certified electrical contractors.
- Lit lamp is extremely hot! Only use switch or plug when turning on or off.
- **Always TURN OFF fitting and allow lamp to cool down before replacing lamp. Only switch on fitting once lamp has been correctly secured into lampholder.**
- Keep fixture away from flammable objects or materials that may burn.
- Remove dust and insects from lamp and surfaces regularly.

#### Cleaning

Do not use abrasive cleaning materials on fixture. Do not wipe suspension set with wet cloth. Dust only. Please be aware that the finishes are delicate and can scuff easily.