

Name Nord XL

Materials Spun Metal, Plastic, Steel, Paint

Suspension Electronic Driver, Lamp, Low profile ceiling canopy and Electrical Flex

Dimensions 530 Ø x 275 H (mm) **Lamp Type** 24 Volt Replaceable lamp

Check lamp type for suitability with your dimming system.

Installation

- Be extremely careful when handling the wall light shade as materials are delicate and can scuff easily. Please leave protective plastic cover on shade while preparing for installation.
- Using a qualified electrical contractor, connect electronic driver or transformer to mains power, connect electrical cable from fixture to driver using the terminal block connected to the wall canopy and heat shrink. Install wall canopy back bracket to wall with appropriate screws. Trim suspension cable to approximate length, allowing additional length for final adjustment. Slide suspension cable through cable adjuster, located on ceiling canopy cover.
- 3 Slide front plate of canopy up the flex to meet the back plate and fix with screw connectors.


PLEASE READ THIS DATA SHEET CAREFULLY PRIOR TO COMMENCING ANY INSTALLATION OF LIGHT FITTINGS. PLEASE CONTACT SATELIGHT IF YOU HAVE ANY QUESTIONS.





+61 3 9399 5805 info@satelight.com.au www.satelight.com.au

nord wall/ceiling (24 Volt)



Check lamp type for suitability with dimming.
All dimensions are in millimetres.

Important Safety Instructions

- Please ensure all installation steps are conducted by certified electrical contractors.
 - Lit lamp is extremely hot! Only use switch or plug when turning on or off.
 - Always TURN OFF fitting and allow lamp to cool down before replacing lamp.
 Only switch on fitting once lamp has been correctly secured into lampholder.
 - Keep fixture away from flammable objects or materials that may burn.
- Remove dust and insects from lamp and surfaces regularly.

Cleanin

Do not use abrasive cleaning materials on fixture. Do not wipe suspension set with wet cloth. Dust only. Please be aware that the finishes are delicate and can scuff easily.