



- Name** Gravatas Collection (with single ES lampholder)
- Materials** Metal Wire Frame, Spun Metal, Plastic, Steel, Paint
- Suspension** Single ES E27 Lampholder, Ceiling Canopy and Electrical Flex
- Dimensions** 470 Ø 470 H (mm)
- Lamp Type** 240Volt: Single ES E27 Lamp
(See table at bottom of page for lamp options and maximum wattages.)

Check lamp type for suitability with dimming. Please ensure lamps are purchased from quality lamp manufacturers such as Philips or Osram. Low quality lamps may not perform as well. Lamps not included. Frosted, warm colour temperature, decorative lamps recommended. To change lamps, ALWAYS switch off power to light fitting, then unscrew lamp from lampholder and replace with same type. Make sure lamp is secured into lampholder prior to light operation.

Installation

- 1 Be extremely careful when handling the pendant shade as surfaces are delicate and can scuff easily. When removing shade from packing box, use two hands to pick up the shade. Please leave protective plastic cover on shade while preparing for installation.
- 2 Slide low profile canopy cover plate down flex. Trim electrical flex to approximate length and feed through cord grip, located on the low profile ceiling plate. Wire electrical flex and mains flex into ceiling bracket junction box. Ensure ceiling plate is correctly earthed to mains earth. Once flex is wired, secure ceiling plate to ceiling with appropriate screws, using the various fixing holes available to suit site specific needs. Slide canopy cover plate back up flex and secure to back plate using earth magnets supplied. Ensure the cord grip has been re-tightened after making adjustment.
- 3 Once suspension is secured, undo skirt on lampholder and slide centre of the shade on.
- 4 Once in place, screw lampholder skirt back on. Do not over-tighten as this may strip the thread on the lampholder.
- 5 If you need to lower or raise the pendant loosen the toothpaste cord grip on the ceiling canopy and feed the flex through till you reach your desired height. Tighten the cord grip to secure the fitting in to place.
- 6 Do not apply force to shades or fixture and remember to remove protective plastic cover prior to turning on.

PLEASE READ THIS DATA SHEET CAREFULLY PRIOR TO COMMENCING ANY INSTALLATION OF LIGHT FITTINGS. PLEASE CONTACT SATELIGHT IF YOU HAVE ANY QUESTIONS.



gravatas pendants (240 volt)



Compact Fluorescent
ES E27 Lamp
(20w max.)



Eco Halogen
ES E27 Lamp
(42w max.)



LED
ES E27 Lamp
(10w max.)

Check lamp type for suitability with dimming.
All dimensions are in millimetres.

Important Safety Instructions

- Please ensure all installation steps are conducted by certified electrical contractors.
- Lit lamp is extremely hot! Only use switch or plug when turning on or off.
- **Always TURN OFF fitting and allow lamp to cool down before replacing lamp. Only switch on fitting once lamp has been correctly secured into lampholder.**
- Keep fixture away from flammable objects or materials that may burn.
- Remove dust and insects from lamp and surfaces regularly.

Cleaning

Do not use abrasive cleaning materials on fixture. Do not wipe suspension set with wet cloth. Dust only. Please be aware that the finishes are delicate and can scuff easily.